

Electric power steering ring comprising a worm gear

Patent Number: ☐ [US6357313](#)
Publication date: 2002-03-19
Inventor(s): APPELYARD MICHAEL (GB)
Applicant(s): TRW LUCASVARITY ELECTRIC STEER (GB)
Requested Patent: ☐ [WO9911502](#)
Application US20000486308 20000501
Priority Number(s): GB19970018574 19970903; WO1998GB02594 19980828
IPC Classification: F16H55/24; B62D5/04
EC Classification: [B62D5/04](#), [F16H57/02F1](#), [H02K7/08B](#)
Equivalents: BR9812044, ☐ [EP1007398](#) (WO9911502),

Abstract


Apparatus for removing the backlash and free-play present between a worm (8) and worm wheel (10) in the gearbox of an electric power assisted steering system is disclosed. The worm (8) is provided on an output shaft (6) from an electric motor (4) and the wheel is provided on another separate shaft (9) (possibly the steering column). The wheel is fixed relative to a housing (1), and the worm is fixed relative to the housing through at least a first and a second support assembly (100, 200). The first support assembly (100) is provided at the end of the output shaft (8) distal from the motor (4) and comprises an eccentric bush (101) which can be rotated to adjust the radial position of the output shaft and hence worm gear. The second support assembly (200) allows for angular movement of the output shaft (6). The first support assembly (100) may be manually rotated or may automatically rotate under a spring force to adjust the amount of free-play

Data supplied from the esp@cenet database - I2



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B62D 5/04, F16H 55/24	A1	(11) International Publication Number: WO 99/11502 (43) International Publication Date: 11 March 1999 (11.03.99)
(21) International Application Number: PCT/GB98/02594 (22) International Filing Date: 28 August 1998 (28.08.98) (30) Priority Data: 9718574.8 3 September 1997 (03.09.97) GB (71) Applicant (for all designated States except US): LUCAS INDUSTRIES PUBLIC LIMITED COMPANY [GB/GB]; Stratford Road, Solihull, West Midlands B90 4LA (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): APPLEYARD, Michael [GB/GB]; 31 Judeland, Chorley, Lancashire PR7 1XJ (GB). (74) Agent: BARKER BRETTELL; 138 Hagley Road, Edgbaston, Birmingham B16 9PW (GB).	(81) Designated States: BR, JP, KR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>	

(54) Title: **ELECTRIC POWER STEERING COMPRISING A WORM GEAR**

(57) Abstract

Apparatus for removing the backlash and free-play present between a worm (8) and worm wheel (10) in the gearbox of an electric power assisted steering system is disclosed. The worm (8) is provided on an output shaft (6) from an electric motor (4) and the wheel is provided on another separate shaft (9) (possibly the steering column). The wheel is fixed relative to a housing (1), and the worm is fixed relative to the housing through at least a first and a second support assembly (100, 200). The first support assembly (100) is provided at the end of the output shaft (8) distal from the motor (4) and comprises an eccentric bush (101) which can be rotated to adjust the radial position of the output shaft and hence worm gear. The second support assembly (200) allows for angular movement of the output shaft (6). The first support assembly (100) may be manually rotated or may automatically rotate under a spring force to adjust the amount of free-play.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

ELECTRIC POWER STEERING COMPRISING A WORM GEAR

This invention relates to improvements in apparatus for eliminating or reducing backlash and/or freeplay between a pair of meshing gears, and
5 in particular between a worm gear and a worm wheel in an electric power assisted steering system.

It is known in the art to provide an electric power assisted steering system of the kind in which an electric motor applies an assistance torque
10 to a steering column in response to a measure of the torque applied to the steering column by the driver of a vehicle. The motor acts upon the steering column through a worm gear and wheel gear with the worm gear being provided on an output shaft of the motor and the wheel being provided on a driven shaft which may comprise a portion of the steering
15 column. The worm and wheel act as a reduction gearbox between the motor and the driven shaft. Such a system will hereinafter be referred to as being "of the kind set forth".

A problem with known steering systems of the kind set forth,
20 particularly where the driven shaft comprises a section of the steering column shaft, is that any free play (backlash) between the teeth of the worm and the teeth of the wheel can result in intermittent knocking noises upon torque load reversal. These noises can arise both as a result of variations in the level or torque applied by the motor and also due to
25 movement of the steering column shaft due to the actions of the driver and vibration in the steering rack due to imperfections in the road surface or poorly balanced road wheels.

The problem of noise and knocking due to backlash, has, in
30 practice been found to be significant even at quite low levels of backlash.

For example, backlash can cause a problem even at levels as low as 0.015mm, whereas the lowest tolerance range for backlash that can typically be achieved during production assembly (without individual piece-by-piece adjustment) is around 0.050mm. In addition, it is known
5 that backlash may increase during use of the system due to wear, by approximately 0.05mm. This is noticeable when plastic gears are used to reduce friction weight and cost. Metallic gears would provide an increased resistance to wear but would not be able to provide the low friction levels and tolerance of marginal lubrication needed to ensure that
10 the unit remains back drivable over its working life.

An object of the present invention is therefore to provide a means of overcoming, at least partially, the problem of backlash within the gears between the worm gear and the wheel gear.

15

According to our invention in an electric power steering system of the kind set forth, the motor output shaft which incorporates a worm gear is supported within a housing by at least two support assemblies spaced axially along the output shaft, a first one of said support assemblies
20 including means to allow radial displacement of an end of the output shaft relative to the wheel gear whilst the other support assembly is adapted to allow angular displacement of the output shaft relative to the housing.

The provision of the support assemblies is advantageous because by
25 allowing radial displacement of at least one end of the output shaft, the spacing between the worm gear and worm wheel can be varied. This allows the free play and backlash in the gearset to be adjusted.

The wheel gear may have a fully-throated or half throated tooth
30 form in which the throat radius is substantially greater than (i.e. "non-

conformal" with) the radius of the worm. Thus, a relatively large degree of variation in the positioning, axially, of the wheel gear relative to the worm gear can be tolerated without producing large changes in backlash and free play - whilst only a small change in the radial displacement
5 between the worm gear and the wheel gear produces a useful change in backlash levels.

An advantage of the non conformal throat form is that it is easier to machine than a conformal throat form because it allows a larger diameter
10 of hob and a more advantageous shape for the cutting teeth.

Preferably, the first one of said support assemblies support the output shaft substantially at its free end, i.e. the end furthest from the electric motor. The other support assembly preferably supports the output
15 shaft at a point in between the motor assembly and the worm gear, perhaps approximately midway along the output shaft.

Preferably, the motor output shaft, worm gear and the worm wheel on the steering column shaft are all provided at least partially within a
20 single common housing.

The first support assembly may comprise a bearing assembly supported in an opening or recess provided eccentrically within a bush. The bush may be located in an opening or recess in the housing. Because
25 the bearing is mounted eccentrically in the bush, rotation of the bush about its centre of rotation causes radial displacement of the output shaft relative to the housing at least where it passes through or enters the bush.

Where the output shaft is supported in at least two support
30 assemblies and the first one is adjusted to provide radial displacement of

the shaft, the angle at which the output shaft will pass through the other support assembly will vary. Accordingly, the other support assembly is adapted to allow a degree of angular displacement.

5 The first support assembly may be manually adjusted to facilitate the radial displacement of the output shaft. For example, the bush may incorporate a flange portion which is secured to the housing. The flange portion may be secured by one or more bolts or screws which pass through elongate openings in the flange. The openings allow the flange
10 (and hence the eccentric bush) to be rotated manually relative to the bolts when the bolts are loosened. Once the correct position is achieved the bolts (or screws or the like) may be tightened to fix the flange securely in place.

15 In an alternative arrangement, the first support means may be adapted to automatically adjust during use to displace the output shaft radially. This could, for instance, allow the shaft to be moved automatically to maintain the free play and/or backlash at a desired level.

20 The automatic adjustment means may comprise a compliant member which is adapted to apply a load between the output shaft and the worm wheel through the worm gear. The load may be of a fixed value or may be adjustable. The compliant member may comprise a tension spring or a compression spring. The spring may be linear or non-linear, ie a clock
25 spring.

 The compliant member may be adapted to exert a force between the housing and the eccentric bush which tends to rotate the bush. The rotation is resisted by the force of the worm gear acting upon the worm
30 wheel. The force exerted by the compliant member is preferably chosen

so that friction between the parts of the support means and the housing is overcome.

The second support assembly may comprise a first plate and a
5 second plate which clamp a bearing race therebetween. Each plate may
include one or more raised protrusions which clamp the center race of the
bearing assembly. Most preferably, each plate has a central bore through
which the output shaft can pass and a pair of diametrically spaced
protrusions either side of the bore facing the bearing assembly when
10 clamped. The bearing assembly is preferably clamped over substantially
its control third portion only by the protrusions so that it can "tilt" or
pivot about the protrusions. Thus, a degree of angular rotation of the
bearing races is possible which allows small tolerance bearings to be
used.

15

The protrusions may be hardened pads, and the bearing races may
have a high axial stiffness to prevent excessive uneven loading of the ball
bearings in the horizontal plane when axial forces act on the bearing.

20 An advantage of the automatic adjustment means is that it
eliminates substantially the need to manually adjust the position of the
output shaft during use, allowing wear in the gearset to be automatically
corrected.

25 In addition the automatic adjustment means, a manual backup may
also be included to enable fine adjustment of the output shaft position to
be achieved.

There will now be described, by way of example only, two embodiments of the present invention with the aid of the accompanying drawings, in which:-

5 **Figure 1** is a cross section view of an electric power assisted steering assembly which includes output shaft support assemblies;

10 **Figure 2** is an end view of a first support assembly which supports the free end of the output shaft of **Figure 1** relative to a housing and allows manual adjustment of output shaft radial position;

Figure 3 is an end view of an alternative first support means which allows automatic adjustment of the output shaft radial position;

15 **Figure 4** shows the forces acting between the teeth of the worm gear and the worm wheel;

20 **Figure 5** shows the forces applied between the worm gear and worm wheel due to application of a biasing force generated by an automatic adjustment means such as the one shown in **Figure 3**; and

Figure 6 shows an alternate arrangement to that shown in **Figure 3**.

25 The operation of the support means of the invention will be explained by way of example. **Figure 1** is an illustration of the component parts of a typical electric power steering system. The system comprises a one piece housing 1 having an opening 2 surrounded by a locating flange 3 upon which a housing 4 for an electric motor is secured.

The motor housing 4 supports a motor stator (not shown) and a motor rotor 5 is supported within the stator. An output shaft 6 which extends at least partially through the motor is attached to the rotor 5 and extends through the opening 2 into the housing 1. Operation of the motor causes the rotor 5, and in turn the output shaft 6 to rotate. The output shaft 6 has a worm gear 8 defined along an intermediate portion.

The output shaft 6 is supported by two support assemblies 100,200. A first support assembly 100 is provided at the free end of the output shaft 6 distal from the motor and is located in an opening 7 of the housing 1 so that it can be accessed from outside the housing. The second support assembly 200 is provided to support the output shaft 6 at a point between the motor rotor and the worm gear 8. A driven shaft 9 extends through the housing 1 orthogonal to the output shaft 6 and supports a wheel gear 10 having a conformal tooth form. The driven shaft 9 is supported within the housing 1 through fixed bearings (not shown) so that it can not be displaced radially relative to the housing. It is held in a position whereby the wheel gear 10 meshes with the worm gear 8 on the output shaft.

20

The first support assembly 100, comprises an eccentric bush 101 having a flange 102 welded into one end. The outer perimeter of the bush 101 is cylindrical and it is adapted to be located within the cylindrical bore 7 in the housing 1 so that the flange 102 abuts an outside face of the housing 1. The free end of the output shaft 6 is supported by a bearing assembly comprising a bearing 103 which is press fitted within an eccentric circular bore 104 in the bush 101. The bearing 103 is fitted so that it is eccentric to the outside circumference of the bush 101 as shown in Figure 2.

30

The outside perimeter of the bush 101 is chosen to be circular so that it can be rotated within the bore 7 in the housing. Of course, it does not need to be circular, and any shape which permits at least a range of rotation of the bush 101 relative to the housing 1 would be acceptable.

5 The bush 101 is secured in position by bolts 105 which pass through elongated slots 106 in the flange. The length of the slots 106 in this case determines the maximum permissible amount of rotation of the bush 101 within the bore 7. Because the flange 102 is located on the outside of the housing 1, it is trivial to alter the position of the flange 102 during use by

10 loosening the bolt, rotating the bush and retightening the bolts 105.

As described hereinbefore, the output shaft 6 is located through a bearing 103 within the first support assembly 100 so that rotation of the bush 101 produces a radial displacement of the worm gear 8 which allows

15 backlash to be adjusted.

The second support assembly 200 is adapted to allow a degree of angular adjustment of the output shaft 6 to accommodate angular misalignment which occurs when the worm gear is radially displaced.

20 The second support assembly 200 comprises a first plate 201 and second plate 202 which clamp either side of a bearing assembly 203 through which the output shaft 6 passes. The plates 201,202 incorporate raised protrusions 210 which are adapted to clamp the outer race of the bearing assembly at its middle third portion only, the bearing being able to "tilt"

25 or pivot around the raised portions. Thus, tight clearance bearings can be employed without causing problems due to out-of-alignment running.

The operation of the adjustment of the backlash and freeplay will now be explained. By way of example, consider that the reduction ratio

30 of the gearset is typically between 12 and 20:1. For this example assume

that it is in fact 16.5:1. Further, assume that the PCD (pitch circle diameter) of the gear wheel is 92.7mm and the tooth pressure angle α is 14° . The PCD of the worm is 15.2mm.

5 The effect of radial movement of the teeth relative to the corresponding female slot is governed by the pressure angle of 14° according to $2 \times \tan 14^\circ \approx 0.5$. Hence, 0.2mm radial adjustment of the worm teeth (i.e. output shaft) will cause a 0.1mm change in backlash. As described hereinbefore, the maximum backlash which may typically be
10 encountered is 0.1mm. Thus, to remove all backlash during the life of the system a radial movement of the tooth meshing point of 0.2mm (i.e. ± 0.1 mm total) is required. Hence, a total of 0.4mm radial adjustment is needed at the first support end of the output shaft. This can be achieved by approximately ± 0.2 mm adjustment of the position of the bearing
15 supporting the output shaft at the first support end. For a typical arrangement this in turn produces a ± 0.05 mm radial displacement of the output shaft at the motor end which is quite acceptable for the running of the motor.

20 The angular rotation of the worm shaft due to this adjustment range is estimated at $\pm 0.115^\circ$, which is accommodated by the second support means which allows small angular misalignment. If no range of misalignment is provided at the second support, for instance by using small tolerance bearings in a fixed support, the bearings would rapidly
25 deteriorate.

To provide for the range of adjustment required, the first support means comprises a cylindrical bush 101 having an eccentric hole into which an output shaft support bearing assembly 103 is located. The
30 bearing 103 is located approximately 2mm off centre (ie eccentricity

x=2mm), and the bush 101 is initially aligned so that rotation of the bush 101 causes maximum vertical displacement (desirable) of the output shaft with minimal horizontal displacement (undesirable). The flange is provided with slots which allow approximately $\pm 6^\circ$ of rotation to provide
5 for the full amount of adjustment required.

In a modification, shown in Figures 3 and 6, first support assembly 100 comprises a bush 301 with a flange 302 in which a portion 303 of the flange 302 is extended radially to define a "lever arm".
10 A compliant member 304 such as a tension spring is connected between the lever arm 303 and a part of the housing 1. Whereas in the first embodiment the position of the flange 101 was fixed relative to the housing by bolts, in this modification the flange 302 is free to rotate under the force of the tension spring. This allows the radial position of
15 the output shaft to be automatically adjusted in use.

The spring force T must be chosen correctly to eliminate free play without increasing wear of the gearset due to excessive force between the worm gear and wheel gear.
20

For example, consider that the distance d between the centre of rotation of the bush 301 and the point on the lever arm 303 at which the spring 304 is attached is 40mm, and the outside diameter OD of the bush is 28mm. The forces acting on the bush 301 due to the spring when no
25 force is exerted by the gearset are shown in Figure 3.

The force T of the spring acting via the lever of 40mm applies $T \times 40\text{N-mm}$ torque to the bush. Assuming a coefficient of friction between the bush and housing of 0.3, this force is resisted by a force T^1 of $T \times 0.3$
30 acting at a distance of 14mm. Thus, the net turning force on the bush is

approximately 36 x TN.mm which causes the worm to fully engage with the flanks of the teeth of the wheel gear. This is shown in Figure 4.

Next, assume that a force F is applied to the gear wheel, for instance as the steering column is rotated by a driver as shown in Figure 4. If this force is, say, 42000 N-mm, a tangential force F^1 of 890N occurs at the gear pitch circle radius (46mm). This results in a gear separating force F^{11} of $890 \times \tan 140 = 222\text{N}$, resisted by a frictional sliding force F^{11} between the teeth of $(1/\cos 140 \times \sin 140 \times 0.05) = 11\text{N}$ (where 0.05 is the coefficient of friction between a plastic gear and a lubricated steel worm). The actual separating force F^{11} is thus 211N.

The vertical reaction force at the outside diameter of the eccentric bush 301 is approximately 105.5N which causes a turning force on the bush of $2 \times 105.5\text{N} = 211\text{N.mm}$ and also a resistance to turning due to the frictional force between the bush 301 and the housing 1 ($= 105.5 \times 0.3 \approx 33\text{N}$) which acts at 14mm radius, giving a resistive torque of $33 \times 14 \approx 460\text{N.mm}$. This is greater than the turning torque on the bush 301 due to the gear separating forces and therefore the teeth remain fully engaged because the bush 301 does not move.

Because of this inherent self-locking action of the eccentric bush, which is due to the large difference between the outer radius of the bush (14mm) and its eccentricity (2mm), the amount of spring tension is not directly relevant to the self-locking behaviour. It can therefore be chosen from consideration of other factors; e.g. how much gear friction torque is acceptable as a result of having the sprung engagement.

The relationship between the gear meshing (engagement) bias force and the effect on gear friction is explained with the aid of Figure 5.

Turning now to Figure 5, if the bias force BF is 100N, then combined flank reaction forces of R will occur at the sides of the tooth where

$$5 \quad R = \frac{100}{\tan^{\circ} x \cos 14^{\circ}} = 413N$$

The sliding force will be $413 \times 0.05N$ acting at a worm pitch radius of 7.6mm, resulting in a worm shaft friction torque of 157 N-mm. As seen at the gear-shaft, this will be equivalent to: $157 \times 16.5/0.86$, where
 10 0.86 is the average efficiency of the gearset.

i.e. output side friction torque due to biasing of worm into gear by
 100N = 3012 N-mm \approx 3.0N-m

15 If max acceptable friction = 0.3N-m, then gear bias force = 10N
 max

Force at bush = 5N

Torque at bush = $5 \times 2 = 10$ N-mm

Force in spring required

$$20 \quad \frac{10}{40} \times \frac{1}{0.9} = 0.28N \quad \text{*allowing for bush friction}$$

This is rather a light spring force.

25 In a second arrangement shown in Figure 6, the bush eccentricity X is increased to 3mm and the lever arm length is reduced to 20mm, (Figure 6).

13

Therefore For gear bias force = 10N,
force at bush = 5N

therefore Torque at bush = $5 \times 3 = 15\text{N-mm}$

5

therefore Net sprung torque on bush = 15N-mm

If spring force = T^{11} , then net torque = $T^{11} \times 20 - T^{11} \times 0.3 \times 14$
 $\approx 16 T' = 15$

10 therefore $T \approx 1\text{N}$

To check that effect of gear separating force on 3mm eccentric bush is still zero movement due to the friction effect:-

15 Vertical reaction at OD of bush

$\approx 105,5\text{ N}$

Turning torque on bush = $3 \times 105,5$
= 316,5 N-mm

Resistance to turning $\approx 460\text{ N-mm}$

20 therefore the Bush still locks.

It will be understood that the present invention relates to apparatus for removing the free play and backlash present between a worm gear and wheel gear in an electric power assisted steering system by providing radial movement of an end of the output shaft. The invention is in no way limited to the exact embodiments described herein, and it is envisaged that several alternatives to the design of the support assemblies which achieve the radial movement of the output shaft will fall within the scope of protection sought.

CLAIMS

1. An electric power steering system in which an electric motor (4) is adapted to apply an assistance torque to a steering column in response to a measure of the torque applied to the steering column by a driver of a vehicle, and the motor acts upon the steering column through a worm gear (8) and a wheel gear (10) with the worm gear being provided on an output shaft (6) of the motor and the wheel gear being provided on a drive shaft (9) characterised in that the motor output shaft (6) which incorporates the worm gear (8) is supported within a housing (1) by at least two support assemblies (100,200) spaced axially along the output shaft, a first one (100) of said support assemblies including means (101) to allow radial displacement of an end of the output shaft relative to the wheel gear whilst the other support assembly (200) is adapted to allow angular displacement of the output shaft (6) relative to the housing (1).
2. An electric power steering system according to claim 1 in which the wheel gear (10) comprises teeth which have a fully-throated or half throated tooth form in which the throat radius is substantially greater than the radius of the worm.
3. An electric power steering system according to any one of claims 1 and 2 in which the first one (100) of said support assemblies is adapted to support the output shaft substantially at its end furthest from the electric motor (4).
4. An electric power steering system according to any preceding claim in which the other support assembly (200) supports the output shaft at a point in between the motor assembly (4) and the worm gear (8).

5. An electric power steering system according to any preceding claim in which the motor output shaft (6), worm gear (8) and the worm wheel (10) on the steering column shaft are all provided at least partially within a single common housing.

5

6. An electric power steering system according to any preceding claim in which the first support assembly (100) comprises a bearing assembly (103) supported in an opening or recess provided eccentrically within a bush (101).

10

7. An electric power steering system according to claim 6 in which the bush (101) is located in an opening or recess in the housing (1).

8. An electric power steering system according to any preceding claim in which the first support assembly (100) is manually adjustable to facilitate the radial displacement of the output shaft (6).

15

9. An electric power steering system according to of claim 6 or 7 in which the bush (101) incorporates a flange portion (102) which is secured to the housing (1).

20

10. An electric power steering system according to claim 9 in which the flange portion (102) is secured by one or more bolts or screws (105) which pass through elongate openings (106) in the flange.

25

11. An electric power steering system according to claim 6 or 7 in which the first support means (100) is adapted automatically to adjust during use to displace the output shaft (6) radially.

12. An electric power steering system according to claim 11 in which the first support means (100) incorporates automatic adjustment means comprising a compliant member (304) which is adapted to apply a load between the output shaft and the worm wheel through the worm gear.

5

13. An electric power steering system according to claim 12 in which the load is of a fixed value.


14. An electric power steering system according to claim 13 in which
10 the compliant member (304) comprises a tension spring or a compression spring.

15. An electric power steering system according to claim 13 or
claim 14 in which the compliant member is adapted to exert a force
15 between the housing (1) and the bush (301) to rotate the bush.

16. An electric power steering system according to any preceding claim
in which the other support assembly (200) comprises a first plate (201)
and a second plate (202) having a bore therethrough through which the
20 output shaft (6) passes and a bearing assembly (203), and in which each of
the plates has a pair of diametrically spaced protrusions (210) facing the
bearing assembly and, adapted so that the bearing assembly is clamped at
its central portion by the protrusions.

25 17. An electric power steering assembly according to claim 16 in which
the bearing assembly (203) is clamped substantially by its central third
portion only.

18. An electric power steering system according to claim 16 in which
30 the protrusions (210) clamp onto an outer race of the bearing assembly.



2/3




Fig. 2




Fig. 3




Fig 6

3/3




Fig. 4




Fig. 5

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 98/02594

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B62D5/04 F16H55/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 B62D F16H H02K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 420 131 A (MAZDA) 3 April 1991 see column 7, line 8 - line 28; figure 1 ---	1,3-5
A	EP 0 270 159 A (BISIACH & CARRU') 8 June 1988 see abstract; figures 1,2 ---	1
A	PATENT ABSTRACTS OF JAPAN vol. 17, no. 306 (M-1428), 11 June 1993 - & JP 05 026330 A (MATSUSHITA), 2 February 1993 see abstract; figures ---	1
A	FR 2 375 572 A (PFLIEGER) 21 July 1978 see page 4, line 25 - line 31; figure 1 ---	1
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

1 December 1998

09/12/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Krieger, P

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 98/02594

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 96, no. 1, 31 January 1996 -& JP 07 237551 A (NIPPON SEIKO), 12 September 1995 see abstract; figures ---	1,6,7
A	US 3 220 277 A (DIXON) 30 November 1965 see column 2, line 11 - line 29; figures 2-5 ---	6-10
A	GB 2 155 583 A (QUICK-SET INCORPORATED) 25 September 1985 ---	
A	EP 0 627 352 A (NSK) 7 December 1994 ---	
A	EP 0 748 735 A (KOYO SEIKO) 18 December 1996 -----	

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/GB 98/02594

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 420131	A	03-04-1991	JP 3112784 A	14-05-1991
			DE 69007396 D	21-04-1994
			DE 69007396 T	10-11-1994
			US 5044454 A	03-09-1991
EP 270159	A	08-06-1988	JP 63149474 A	22-06-1988
			US 4827790 A	09-05-1989
FR 2375572	A	21-07-1978	NONE	
US 3220277	A	30-11-1965	NONE	
GB 2155583	A	25-09-1985	US 4586393 A	06-05-1986
			DE 3507968 A	12-09-1986
EP 627352	A	07-12-1994	US 5482127 A	09-01-1996
EP 748735	A	18-12-1996	JP 9002298 A	07-01-1997
			US 5738183 A	14-04-1998